

AJN Ex

Transmitting unit

AJN Ex is the most compact model of the Ex series, designed for the safe and reliable control of machines operating in potentially explosive atmospheres. It has been developed for complex industrial applications and combines functional safety, robustness, and ergonomics in a single solution. AJN Ex is suitable for use in ATEX gas and dust areas classified as Zone 1, Zone 21, Zone 2, and Zone 22, as well as for mining applications in category M1, where the remote control must ensure consistent performance even under harsh environmental condition.

EX Ex series



Safety functions
GSS, EMS, ATS (EN 62745)



ATEX zone
Zone 1-21, mining M1 or Zone 2-22



Data Feedback
2.8" display



Max number of joysticks
Up to 2 multi-axis



Compatible receiving units
All receivers in Air series





Discover more


Technical data

Power supply	3.7 VDC
Radio frequency	870/915 MHz FHSS
Performance level of stop (GSS / EMS)	up to PL d, SIL 2 (EN ISO 13849-1)
Performance level of the automatic stop (ATS)	up to PL d, SIL 2 (EN ISO 13849-1)
Typical working range	100 m (330 ft)
Max number of functions	up to 2 multi-axis joysticks, up to 10 actuators and 2 side pushbuttons
Average usage time with fully charged battery (continuous use at 20°C / 68°F)	without display: 20 hours with display: 8 hours
Protection degree	IP65 (NEMA 4)
Operating and storage temperature	operating: (-20 °C) ÷ (+60 °C) / (-4 °F) ÷ (+140 °F) storage: (-40 °C) ÷ (+70 °C) / (-40 °F) ÷ (+158 °F)
Dimensions	243x163x175 mm (9.57x6.42x6.89 in)
Weight	1,75 kg (3.8 lb)
Included accessories	shoulder or waist belt, battery charger, 2 extractable Li-Ion batteries

ATEX marking

Zone 1/21, mining M1	II 2GD Ex ia IIC T4 Gb Ex ia IIIC T135°C Db I M1 Ex ia I Ma -20°C ≤ Tamb ≤ +60°C
Zone 2/22	II 3GD Ex ic IIC T4 Gc Ex ic IIIC T135°C Dc -20°C ≤ Tamb ≤ +60°C

Options



Environment marine protection



2.8" display

Cert. UNI EN ISO 9001:2015 No. 50 100 2877 Design, manufacture and service of remote control systems for safety industrial application.

This documentation includes general descriptions and/or technical features of the Autec products within. This documentation is not intended to be used as a substitute for, nor is it sufficient for, assessing whether these products are suitable for the user's specific applications. The owner, facility-operator, user and system integrator are responsible for carrying out correct and complete fitness and risk analysis to evaluate and test the specific products and systems with regard to the particular application or use thereof. Neither Autec nor any of its group companies or affiliates shall be responsible or liable for the improper use of the information contained herein.

AUTEC Srl

Via Pomaroli, 65 - 36030 Caldogno (VI) - Italy
Tel. +39 0444 901000 - Fax +39 0444 901011
info@autecsafety.com - www.autecsafety.com

