

AJQ Ex

Transmitting unit

AJQ Ex is the most versatile transmitter unit in a medium-sized format of the Air Ex series. It is designed for safe and reliable control of machines operating in potentially explosive atmospheres. Developed for complex industrial applications, it combines functional safety, robustness, and ergonomics in a single solution. AJQ Ex is suitable for use in ATEX gas and dust areas classified as Zone 1, Zone 21, Zone 2, and Zone 22, as well as for mining applications in category M1, where the remote control must ensure consistent performance even under harsh environmental conditions.



Ex series



Safety functions

GSS, EMS, ATS (EN 62745)



ATEX zone

Zone 1-21, mining M1 or Zone 2-22



Data Feedback

2.8", 4.3" displays



Max number of joysticks

Up to 3 multi-axis or 6 single-axis



Compatible receiving units

All receivers in Air series





Discover more


Technical data

Power supply	3.7 VDC
Radio frequency	870/915 MHz FHSS
Performance level of stop (GSS / EMS)	up to PL d, SIL 2 (EN ISO 13849-1)
Performance level of the automatic stop (ATS)	up to PL d, SIL 2 (EN ISO 13849-1)
Typical working range	100 m (330 ft)
Max number of functions	up to 3 multi-axis joysticks, 8 actuators and 4 side buttons; up to 6 single-axis joysticks, 10 actuators and 4 side buttons
Average usage time with fully charged battery (continuous use at 20°C / 68°F)	without display: 20 hours with display: 8 hours
Protection degree	IP65 (NEMA 4)
Operating and storage temperature	operating: (-20 °C) ÷ (+60 °C) / (-4 °F) ÷ (+140 °F) storage: (-40 °C) ÷ (+70 °C) / (-40 °F) ÷ (+158 °F)
Dimensions	310×159×173 mm (12.2×6.3×6.8 in)
Weight	~2,8 kg (~ 6.2 lb)
Included accessories	shoulder or waist belt, battery charger, 2 extractable Li-Ion batteries

ATEX marking

Zone 1/21, mining M1	II 2GD Ex ia IIC T4 Gb Ex ia IIIC T135°C Db I M1 Ex ia I Ma -20°C ≤ Tamb ≤ +60°C
Zone 2/22	II 3GD Ex ic IIC T4 Gc Ex ic IIIC T135°C Dc -20°C ≤ Tamb ≤ +60°C

Options



Environment marine protection



2.8" display



4.3" display

Cert. UNI EN ISO 9001:2015 No. 50 100 2877 Design, manufacture and service of remote control systems for safety industrial application.

This documentation includes general descriptions and/or technical features of the Autec products within. This documentation is not intended to be used as a substitute for, nor is it sufficient for, assessing whether these products are suitable for the user's specific applications. The owner, facility-operator, user and system integrator are responsible for carrying out correct and complete fitness and risk analysis to evaluate and test the specific products and systems with regard to the particular application or use thereof. Neither Autec nor any of its group companies or affiliates shall be responsible or liable for the improper use of the information contained herein.