

# AXT

## Receiving unit

The AXT is an analog receiving unit from the Dynamic+T series. The Triband technology provides three frequency bands in a single module, which can be used in accordance with local regulations. The pairing procedures between the transmitter/receiver units and the frequency switching can be performed via radio. It features 2 STOP outputs, 2 STOP or UMFS outputs, up to 28 analog outputs and up to 40 digital outputs. The AXT also features a 4-digit display for diagnostics and can be integrated into a Take&Release system. The standard antenna is internal; an external antenna with a 1 m or 3 m extension is available as an option. This receiver provides maximum flexibility through the CODESYS® development environment, the standard for programming according to IEC 61131-3.

**DYN** Dynamic+T series

**Safety functions**  
GSS, EMS, ATS, UMFS (EN 62745)

**Triband radio**  
870 MHz / 915 MHz / 2.4 GHz

**Number of outputs**  
2 STOP, 2 STOP or UMFS, up to 28 analog and up to 40 digital

**Communication protocols**  
CANopen, J1939

**Programmability**  
CODESYS®





Discover more

## Technical data

Power supply	8-30 VDC
Configurable radio frequency	870 MHz 915 MHz 2.4 GHz
Performance level of stop (GSS / EMS)	up to PL e, SIL 3 (EN 13849-1)
Performance level of the automatic stop (ATS)	up to PL e, SIL 3 (EN 13849-1)
Performance level of Unintended Movements From Standstill (UMFS)	up to PL d, SIL 2 (EN 13849-1)
Number of outputs	2 STOP, 2 STOP or UMFS, up to 28 analog and up to 40 digital
Rated current of the command outputs	3A
Rated current of STOP/ UMFS outputs	3A
Connecting interfaces	M12 8 or 5 pin connector, Harting 32 / 40 / 50 / 72 pin connector
Type of output	digital - PWM - voltage - 2 CAN outputs
Communication protocols	CANopen, J1939
Antenna	internal, optional external
Expansion boards	up to 3 proportional
Protection degree	IP65
Operating and storage temperature	operating: (-25 °C) ÷ (+70 °C) / (-13 °F) ÷ (+158 °F) storage: (-40 °C) ÷ (+85 °C) / (-40 °F) ÷ (+185 °F)
Dimensions	240×186×83 mm (9.45×7.32×3.27 in)
Weight	1,2 kg (2.65 lb)

### Cert. UNI EN ISO 9001:2015 No. 50 100 2877 Design, manufacture and service of remote control systems for safety industrial application.

This documentation includes general descriptions and/or technical features of the Autec products within. This documentation is not intended to be used as a substitute for, nor is it sufficient for, assessing whether these products are suitable for the user's specific applications. The owner, facility-operator, user and system integrator are responsible for carrying out correct and complete fitness and risk analysis to evaluate and test the specific products and systems with regard to the particular application or use thereof. Neither Autec nor any of its group companies or affiliates shall be responsible or liable for the improper use of the information contained herein.